

Appln. No. 10/648,895
Amendment
Reply to Office Action dated March 25, 2005

Docket No. 9585-4

AMENDMENTS TO THE SPECIFICATION

In the Title:

MULTIFUNCTIONAL LAMP WITH THE ACOUSTIC OPTICAL SIREN
ILLUMINATION DEVICE AND SIREN, HAVING A PULL-ROPE ACTIVATION

In the paragraph on page 1, lines 6-7

The present invention relates to a ~~kind-type~~ of hand-held lamp, and also relates to ~~the~~ a lamp powered by ~~the~~ battery or commercial electric ~~electricity~~.

In the paragraph on page 1, lines 10-12

The purpose of the present invention is to provide a ~~kind-of-an~~ improved design to this ~~kind-type~~ of lamp. ~~Which, and which~~ could provide to the user with a ~~energy saving, savings, be~~ easy to ~~take-carry and asking~~ enable a user to ask for help by ~~the~~ using a siren.

In the paragraph on page 1, lines 14-20

According to the present invention, it ~~there~~ is provided with a ~~kind-type~~ of lamp, which includes a lamp body with at least three light sources, and siren and a rope ring ~~held-by-handle~~. The lamp body has an inner chamber with a focus lamp unit chamber disposed at its upper end, a cold cathode lamp unit chamber at the front end of the lamp body and a flash lamp unit chamber at the back end of the lamp body. An electric source circuit is accommodated in the inner chamber of the lamp body and the siren is operable by a hand-held rope. The said-light source could-can illuminate continuously over two days with the power supplied by the general battery, and also does not need to replace the lamp within 100,000 hours in use, which could. The lamp can provide to the user with a ~~energy saving, savings, it is~~ easy to ~~take-carry and asking~~ can ask for help by use of the siren.

In the paragraphs on page 1, line 22- page 2, line-9

The additional technical features of the present invention are explained in details as follows in combination with the drawings, in which:

~~The~~ Fig 1 is the side view of the lamp according to the present invention;

(WP243147;1)

Appln. No. 10/648,895

Docket No. 9585-4

Amendment

Reply to Office Action dated March 25, 2005

~~The~~ Fig 2 is the longitudinal sectional view of the lamp shown in Fig 1;

~~The~~ Fig 3 is the top view of the lamp shown in Fig 1;

~~The~~ Fig 4 is the bottom view of the lamp shown in Fig 1;

~~The~~ Fig 5 is the front view of the lamp shown in Fig 1;

~~The~~ Fig 6 is the back view of the lamp shown in Fig 1;

~~The~~ Fig 7 is another side view of the lamp shown in Fig 1.

In the paragraphs on page 2, line 11- page 4, line-17

The lamp of the present invention generally includes the lamp body (1) ~~in euboid having a rectangular~~ shape, a light source (2) ~~being disposed~~ at the upper end in the lamp body, a viewfinder surface (3) ~~in having a~~ paraboloid shape and a projecting plate (4) made of glass or other transparent material, ~~the~~ The viewfinder surface (3) and the projecting plate (4) form a focus lamp unit chamber. The projecting plate (4) is generally in the a paraboloid shape and has the function functions for convergeneing converging the light source. The inner side surface of the said projecting plate (4) is sealed with the end surface within ~~the a~~ front ring-shape lamp cap (5) which is mounted on the upper end of the lamp body (1). ~~The one One~~ end of the lamp body (1) has ~~euboid an elongated~~ light source (6), and a viewfinder (7) which is generally as a flat surface for reflecting and strengthening the light source, the and a light -permeating cover (8) is-made of glass or other transparent material, the said light-permeating cover (8) is-being disposed at the front end of the lamp body (1).-The light source (6) is preferably a fine and long-life cold cathode fluorescent lamp, which does not need to be replaced. The viewfinder (7) and the light-permeating cover (8) form a cold cathode lamp unit chamber.

A flash light cover (10), which is made of the glass , other transparent material or semi-transparent material, the covers a lamp bulb. The flash light cover (10) has the a ball body (11) for diffusing the refraction, which could make-scatters the refraction of the light source-being scattered, and the. The flash light cover (10) is disposed at the back end of the light body (1). The flash light cover (10) forms a flash lamp unit chamber with a surface provided underneath the lamp.

Appln. No. 10/648,895
Amendment
Reply to Office Action dated March 25, 2005

Docket No. 9585-4

As shown in the Figs, at least three light sources of the light body (1) are lamps which are powered by the electrical source (12) in the light body (1), ~~the~~ The electrical source is connected with ~~the an~~ an electrical source circuit (13) in the lamp body (1) through ~~the an~~ an electrical line and connected to ~~the an~~ an outside socket (15), ~~and the kinetic~~ A kinetic energy switch (14) is connected with the lamp. Obviously, the light source could be powered by battery or by rechargeable battery, the direct electrical source is connected with charger, and the electrical source circuit in the lamp body (1) is for charging. The lamps emit light but do not generate heat, thus making the lamp safe and even suited for little children.

As shown in the Figs, there is a battery ~~gate-hatch~~ at the lower end of the lamp body (1), the ~~said battery gate-hatch~~ (16) is the entrance and exit of the battery, ~~the~~ A contacting metal plate (17) at the upper end of the battery ~~gate-hatch~~ (16) is for turning on the battery. The battery ~~gate-hatch~~ (16) is detachably fixed at the lower end of the lamp body (1).

The lamp body can include a ring made of rubber or other elastic material at the upper and lower ends, the rubber ring making it easy for a user to hold the lamp, and providing shock resistance to the lamp body.

There is a pull switch button (18) at the upper end of the lamp body (1), and a rope (19) held by ~~hand-handle~~ hand-handle is linked at the end of the said pull switch button (18). The ~~said pull switch button~~ (18) is detachably fixed at the upper end of the lamp body (1). ~~The metal-elastic~~ Metal deformable plates (20) and (21) are separated while the pull switch button (18) being fixed at the upper end of the lamp body (1), but when the pull switch button (18) is separated from the lamp body (1), the metal ~~elastic-deformable~~ plates (20) and (21) are jointed together due to the elasticity of the metal itself, therefor the electric energy is generated to turn on the siren and which leads to the buzzer (9) to sound an alarm. Thus, when the user of the lamp is in ~~the a~~ dangerous situation, the pull switch button (18) of the rope ~~held by hand-handle~~ is pulled by the user, then the siren sends the information of asking for help.

In other words, the multi-functional cold cathode lamp of the present invention could be used as flashlight, and is also easy to hold by hand or to ~~load-carry~~ carry in ~~the a person's~~ a person's pocket, ~~the~~ The multi-functional cold cathode lamp of the present invention ~~could be used as the flashlight which~~
(WP243147;1)

Appln. No. 10/648,895

Docket No. 9585-4

Amendment

Reply to Office Action dated March 25, 2005

~~focuses~~ can focus illumination ~~in-over~~ a long distance, and ~~illuminates~~ can illuminate in different angles ~~in-over~~ a short distance, and ~~sends~~ can send signal light in different frequencies, ~~which~~.
This is very useful for protecting ~~the lady'~~ women's safety or for ~~the people to travel~~.

5 **ILLUMINATION DEVICE AND SIREN, HAVING A PULL-ROPE
ACTIVATION**

FIELD OF THE INVENTION

The present invention relates to a type of hand-held lamp, and also relates to a lamp powered by battery or commercial electricity.

OBJECT OF THE INVENTION

- 10 The purpose of the present invention is to provide an improved design to this type of lamp, and which could provide to the user with energy savings, be easy to carry and enable a user to ask for help by using a siren.

SUMMARY OF THE INVENTION

- 15 According to the present invention, there is provided a type of lamp, which includes a lamp body with at least three light sources, and siren and a rope ring handle. The lamp body has an inner chamber with a focus lamp unit chamber disposed at its upper end, a cold cathode lamp unit chamber at the front end of the lamp body and a flash lamp unit chamber at the back end of the lamp body. An electric source circuit is accommodated in the inner chamber of the lamp body and the siren is operable by a hand-held rope. The light source can illuminate continuously over two days with the power supplied by the general battery, and also
20 does not need to replace the lamp within 100,000 hours in use. The lamp can provide to the user with energy savings, it is easy to carry and can ask for help by use of the siren.

BRIEF DESCRIPTION OF THE DRAWINGS

The additional technical features of the present invention are explained in details as follows in combination with the drawings, in which:

- Fig 1 is the side view of the lamp according to the present invention;
Fig 2 is the longitudinal sectional view of the lamp shown in Fig 1;
5 Fig 3 is the top view of the lamp shown in Fig 1;
Fig 4 is the bottom view of the lamp shown in Fig 1;

{WP243259,1}

Fig 5 is the front view of the lamp shown in Fig 1;

Fig 6 is the back view of the lamp shown in Fig 1;

Fig 7 is another side view of the lamp shown in Fig 1.

10 DESCRIPTION OF THE PREFERRED EMBODIMENT

The lamp of the present invention generally includes the lamp body (1) having a rectangular shape, a light source (2) disposed at the upper end in the lamp body, a viewfinder surface (3) having a paraboloid shape and a projecting plate (4) made of glass or other transparent material. The viewfinder surface (3) and the projecting plate (4) form a focus lamp unit chamber. The projecting plate (4) is generally in a paraboloid shape and functions for converging the light. The inner side surface of the projecting plate (4) is sealed with the end surface within a front ring-shape lamp cap (5) which is mounted on the upper end of the lamp body (1). One end of the lamp body (1) has an elongated light source (6), and a viewfinder (7) which is generally a flat surface for reflecting and strengthening the light source, and a light-permeating cover (8) made of glass or other transparent material, the said light-permeating cover (8) being disposed at the front end of the lamp body (1).
15 The light source (6) is preferably a fine and long-life cold cathode fluorescent lamp, which does not need to be replaced. The viewfinder (7) and the light-permeating cover (8) form a cold cathode lamp unit chamber.

A flash light cover (10), which is made of glass, other transparent material or semi-transparent material covers a lamp bulb. The flash light cover (10) has a ball body (11) for diffusing the refraction, which scatters the refraction of the light source. The flash light cover (10) is disposed at the back end of the light body (1).
5 The flash light cover (10) forms a flash lamp unit chamber with a surface provided underneath the lamp.

As shown in the Figs, at least three light sources of the light body (1) are lamps which are powered by the electrical source (12) in the light body (1). The electrical source is connected with an electrical source circuit (13) in the lamp body (1) through an electrical line and connected to an outside socket (15). A kinetic

10 {WP243259;1}

energy switch (14) is connected with the lamp. Obviously, the light source could be powered by battery or by rechargeable battery, the direct electrical source is connected with charger, and the electrical source circuit in the lamp body (1) is for charging. The lamps emit light but do not generate heat, thus making the lamp safe and even suited for little children.

As shown in the Figs, there is a battery hatch at the lower end of the lamp body (1), the battery hatch (16) is the entrance and exit of the battery. A contacting metal plate (17) at the upper end of the battery hatch (16) is for turning on the battery. The battery hatch (16) is detachably fixed at the lower end of the lamp body (1).

20 The lamp body can include a ring made of rubber or other elastic material at the upper and lower ends, the rubber ring making it easy for a user to hold the lamp, and providing shock resistance to the lamp body.

There is a pull switch button (18) at the upper end of the lamp body (1), and a rope (19) handle is linked at the end of the said pull switch button (18). The pull switch button (18) is detachably fixed at the upper end of the lamp body (1). Metal
5 deformable plates (20) and (21) are separated while the pull switch button (18) being fixed at the upper end of the lamp body (1), but when the pull switch button (18) is separated from the lamp body (1), the metal deformable plates (20) and (21) are jointed together due to the elasticity of the metal itself, therefor the electric energy is generated to turn on the siren and which leads to the buzzer (9) to sound an alarm. Thus, when the user of the lamp is in a dangerous situation, the pull switch button (18) of the rope handle is pulled by the user, then the siren sends the
10 information of asking for help.

In other words, the multi-functional cold cathode lamp of the present invention could be used as flashlight, and is also easy to hold by hand or to carry in a person's pocket. The multi-functional cold cathode lamp of the present invention can focus illumination over a long distance, and can illuminate in different angles over a short distance, and can send signal light in different frequencies. This is very useful for
15 protecting women's safety or for people when traveling.

{WP243259;1}